



Never compromise on quality!



# S3 SANITARY SEALANT

## High Performance Silicone Sealant

### Description

*A high performance, low maintenance, fungal resistant silicone sealant.*

One part silicone sealant with excellent adhesion to ceramics, glass, melamine laminates and sanitary plastics. **S3 SANITARY SILICONE** is also compatible with anodised aluminium and lacquered metals. Bond It **S3 SANITARY SILICONE** contains a biocide to prevent unsightly mould growth. Conforms to EN 15651-1,3:2012.

### Uses

Bond It **S3 SANITARY SILICONE** should be used for sealing around worktops, basins, sinks, bed basins to vanity units and also to seal shower trays and shower units. It has been specially designed to seal in damp and humid areas.

It is ideal for use on:

- ◆ glass
- ◆ ceramics
- ◆ anodised aluminium
- ◆ lacquered metals
- ◆ painted timber
- ◆ painted plaster
- ◆ sanitary plastics
- ◆ primed or painted concrete
- ◆ primed metals

### Preparation

Ensure all surfaces are clean, dry and free from grease or any contaminants that may hinder adhesion. Remove any old sealant.

### Application

Apply using a standard sealant gun with the nozzle cut at an angle of 45°, and to an opening slightly larger than the joint to be sealed.

**For bath surrounds:** Third fill the bath with water to allow sealant to be applied at joint mid point. If necessary masking tape may be applied. If large gaps are to be filled, polythene foam, rod or tape should be used to provide support and minimise sealant wastage. Tool down within 5 minutes using a wet spatula. Any trims should be bedded into the silicone within 5 minutes.

**For sealing waste outlets in sinks and baths: S3**

**SANITARY SILICONE** should be applied so that it will be in compression after tightening of connecting pipes.

**For metallised plastic trims:** test for discolouration by sealant before use.

### Limitations

Do not use on bare metal or fresh concrete without priming. Natural stone, particularly marble must be protected by primer/sealer. Not suitable for mirrors. For fixing mirrors use Bond It LN7 or MIRROR-MATE.

### Container Size

EU3 plastic cartridge.

### Colours

**S3 SANITARY SILICONE** comes in 3 colours: white, translucent and ivory.

### Shelf Life

24 months in unopened cartridges.

### Storage Conditions

Store in cool, dry conditions between +5 and +30°C.

### Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Remove any containers to a central disposal point in accordance with local regulations.

### Health & Safety

- ◆ Avoid eye contact.
- ◆ Avoid prolonged contact with skin.
- ◆ Thoroughly wash hands with soap and water after use.
- ◆ Keep out of reach of children.
- ◆ See separate material safety data sheet for full handling, use and storage.

## Specification Summary

Tooling Time	5-10 minutes
Skimming Time	15 minutes
Drying Time	3mm depth per day
Movement Capability	±25%

### Container Sizes:

<b>Colour:</b>	Ivory	White	Transluscent
<b>Code:</b>	BDS3IV	BDS3WH	BDS3T
<b>Size:</b>	EU3	EU3	EU3
<b>Barcode:</b>	5060021360472	5060021360496	5060021360489



**BOND IT**  
G16 River Bank Way, Lowfields Business  
Park, Elland, West Yorkshire. HX5 9DN

14

**EN15651-1,3:2012**  
F EXT-INT S1  
Facade sealant for exterior and interior  
use. Sanitary sealant.

<b>Reaction to fire</b>	E
<b>Release of chemicals</b>	None
<b>Resistance to flow</b>	≤ 3mm
<b>Loss of volume</b>	≤25%
<b>Tensile properties after water immersion</b>	NF
<b>Durability</b>	Pass
<b>Microbiological growth</b>	S1

*The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.*



Certificate Number: 6152  
ISO 9001  
ISO 14001



**BOND IT**  
Unit G16 River Bank Way, Lowfields Business Park, Elland,  
West Yorkshire HX5 9DN.  
Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310  
Email: sales@bond-it.co.uk Website: www.bond-it.co.uk



V4 20/08/14  
Supersedes V4 09/07/14