

# Radex Radon Tape

Version No.2

Revision Date: 21/04/2016

Page 1 of 2

## DESCRIPTION

Radex Radon Tape is a general purpose butyl tape.

## KEY FEATURES

Good adhesion to a wide range of substrates.

Good UV resistance.

The softer composition makes this product highly conformable.

Easy and accurate to use with little waste and no mess.

High tack.

Remains flexible throughout its service life.

## USES

For use as an air, dust or water seal for compression joints and seams.

For water sealing applications in vehicle construction.

Sealing membranes such as Radon

## PERFORMANCE

	UNIT	NOMINAL VALUE	TEST METHOD
Dynamic Tensile Adhesion	N/cm <sup>2</sup>	32	H5
Dynamic Shear Adhesion	N/cm <sup>2</sup>	12	H15
90° Peel Adhesion	N/cm	8	H48
180° Peel Adhesion	N/cm	9	H41
Specific Gravity	g/cm <sup>3</sup>	1.6	H6
Moisture Vapour Transmission Rate	g/m <sup>2</sup> /24hr/mm	0.14	ISO9932 / BS ISO 15106
Radon Resistance	Z, s/m	5 x 10 <sup>7</sup>	SP 3873
Service Temperature Range	°C	-40 to +90	

H - Manufacturer's Test Method



Unit 3, Allied Industrial Estate, Kylemore Road  
01 642 6600 sales@laydex.ie www.laydex.ie

# Radex Radon Tape

Version No.2

Revision Date: 21/04/16

Page 2 of 2

## APPLICATION

### PROPERTIES

**Application temperature range:** +5°C to +40°C

**Shelf life:** 24 months when stored flat in original packaging in cool, dry conditions.

### INSTRUCTIONS

**Surface preparation:** All surfaces should be clean, dry and free from frost, grease and loose materials. When cleaning contaminated substrates, HS Butyl recommend that propan-2-ol (IPA) is used and allowed to dry prior to the application of the butyl tape.

**Application:** Apply direct from the reel onto one surface and press sufficiently along its whole length to achieve good initial adhesion. Remove backing paper and offer other surface to the sealant and push firmly to seal across the joint.

## PACKAGING

The product is normally supplied as an extruded strip on a siliconised release paper. A wide range of dimensions can be supplied. Product dimensions will determine the number of rolls per carton.

Available colours: Black, grey and white.

## TOLERANCES

Rectangular sections:

Thickness  $\pm 10\%$

Width: up to 25mm  $\pm 1\text{mm}$

26mm to 100mm  $\pm 2\text{mm}$

over 100mm  $\pm 3\text{mm}$

Bead sections:

Thickness  $\pm 10\%$

Width  $\pm 10\%$

## GENERAL

0305 butyl tape is part of a range of butyl products for Construction and Automotive markets. For further information, please contact our Customer Care Team or visit our Website.

*The information given in this product data sheet is based on laboratory tests and experience which we believe to be correct. Properties quoted are typical and do not therefore constitute a specification. In view of the wide range and variability of substrates, we would advise that our product should be tested by the user to establish suitability for its intended application. E &OE.*

