

Ultima Twist Specification Guide

Ultima Twist				
Quality Type	Gold Talisman Talana	Trident	Fontaine Major Ultima	Penultima
Suitability	Heavy Duty Contract Extra Heavy Duty Residential	Light Duty Contract Heavy Duty Residential	Heavy Duty Contract Extra Heavy Duty Residential	Light Duty Contract Medium Duty Residential
Widths	1m, 3.66m(12ft) 4m, 4.57m(15ft) & 5m	1m, 3.66m(12ft) 4m, 4.57m(15ft) & 5m	1m, 3.66m(12ft) 4m, 4.57m(15ft) & 5m	1m, 3.66m(12ft) 4m, 4.57m(15ft) & 5m
Composition Yarn	80/20 Wool Nylon 2 Fold Yarn	80/20 Wool Nylon 2 Fold Yarn	80/20 Wool Nylon 2 Fold Yarn	80/20 Wool Nylon 2 Fold
Tufted Construction	1/10th Gauge	1/10th Gauge	1/8th Gauge	1/8th Gauge
Stitch Rate*	11, 10.25 & 10.25 S/in	8.25 S/in	9.5, 10.5 & 9.75 S/in	8.5 S/in
Pile Height Above Backing*	11.5mm, 7mm & 5.5mm	5.5mm	9.5mm, 7.5mm & 6.5mm	5.5mm
Total Carpet Thickness*	13.5mm, 9mm & 7.5mm	7.5mm	11.5mm, 9.5mm & 8.5mm	7.5mm
Primary Backing	Polypropylene	Polypropylene	Polypropylene	Polypropylene
Flammability BS4790 Hot Nut Test	Low Radius of Char	Low Radius of Char	Low Radius of Char	Low Radius of Char
Light Fastness BS1006	Min 4 to 5	Min 4 to 5	Min 4 to 5	Min 4 to 5
Rubbing Fastness BS1006	4 Wet 3 Dry	4 Wet 3 Dry	4 Wet 3 Dry	4 Wet 3 Dry
Colour Fastness BS1006 % Shampoo	4	4	4	4
Castor Chair Rating DIN54324	Pass	Pass	Pass	Pass
Dimensional Stability ISO 2551	Pass	Pass	Pass	Pass
Surface Flammability Ceilings, bulkhead & deck IMO 653(16)	Pass	Pass	Pass	Pass
Sound Absorbtion BS EN ISO 354:2003, BS EN ISO 11654:1997, ATSM C423-01	Class C	Class C	Class C	Class C
Tog Rating	1.96/1.66/1.45	1.37	1.67/1.62/1.45	1.37

* +/- 10% commercial tolerance



ULTIMA CLASSIC

Ultima Twist Berber carpets separated out from the main range. The tweed effect makes this colour much more suitable for commercial use where a serviceable carpet is essential. Look for the * symbol on the colour pallet on pages 24 and 25.