

Corotop® EXTRA PROTECT 165

An extremely durable four-layer roof membrane produced in the „hot melt” process. Usage of the mesh and additional layer of vlies guarantee great resistance parameters. The membrane is recommended to clients searching strong and durable products providing prolonged roof liveness.

Application:

- the membrane dedicated on roofs with full or part-boarding
- initial underlay for thermally insulated, ventilated, sloping roofs
- to be used to most types of roof coverage, particularly under ceramic and metal tiles

Advantages:

- strengthened with a special polypropylene mesh
- minimizes heat loss
- regulates two-way vapour permeability
- the product with very high resistance to any damages
- also available in version with 2 adhesive stripes (Corotop Extra Protect 165+)



GRAMMATURE
165 g/m²



REACTION TO FIRE
CLASS E



VAPOUR
PERMEABILITY (SD)
0,07 m



RESISTANCE TO WATER
PENETRATION
CLASS W1



RESISTANCE TO UV
3 MONTHS



RESISTANCE TO TEARING
(NAIL SHANK) ALONG/ACROSS:
350 N / 380 N

Name	Size	Colour	Package
Corotop® EXTRA PROTECT 165	1,5m x 50r.m. = 75m ²	blue and white	20 rolls
Corotop® EXTRA PROTECT 165+	1,5m x 50r.m. = 75m ²	blue and white	20 rolls